

Ordinary Portland Cement (OPC) Grouting Unit



Continuous mixing and pumping unit for large volume grout applications. Housed in one (1) DNV certified frame for ease of mobilisation.

APPLICATIONS

Jacket pile grouting, drilled pile annulus grouting, offshore wind farms, grout bags.

COMPONENTS

- Centrifugal mixing pump
- Progressive cavity pump
- Mixing motor
- Densitometer
- Rotary valve
- Water meters/flow control
- Mixing tanks

PROPERTIES

Grout Density (kg/m ³)	Yield (m ³ /Te)	Output (m ³ /hr)
1900 to 2350	0.77 to 0.69	0 - 30

SERVICES REQUIRED

Power	Air	Sea Water
440v, 60Hz, 250 Amp, 480 Amp	100 CFM @ 6.9 Bar	450 Litres/Min @ 7.5 Bar



Exclusively distributed by:



Headquarters:

IEV GROUP SDN BHD
Level 5, Block A, Menara PKNS No. 17,
Jalan Yong Shook Lin, 46050 Petaling Jaya,
Selangor, Malaysia.

T : +6 (03) 7931 9921
F : +6 (03) 7931 9964
W : www.iev-group.com
E : info@iev-group.com

Vietnam:

IEV VIETNAM LLC
214 Nguyen Van Huong Street
Thao Dien Ward, Thu Duc City,
Ho Chi Minh City, Vietnam.

T : +84 28 3997 0196
F : +84 28 3997 0197
W : www.iev-group.com
E : ievvni@iev-group.com